



中国船级社
CHINA CLASSIFICATION SOCIETY
工厂认可证书

证书编号/Certificate No.
JS24PWA00212_01

CERTIFICATE OF WORKS APPROVAL

兹证明本证书所述制造厂具备按照下列标准的要求生产本证书所列产品的能力和条件。

This is to certify that the manufacturer stated in the certificate meets the requirements of the standards listed below and is available with the ability and conditions to produce the products described in the certificate.

制造厂/Manufacturer

安徽天康（集团）股份有限公司
Anhui Tiankang (Group) Shares Co., Ltd

地址/Address

安徽天长市仁和南路20号
No. 20, South Renhe Road, Tianchang, Anhui

产品名称/Product

船用低压电力电缆
Shipboard Low Voltage Power Cable

附加标志/Notations

无/Nil.

认可标准/Approval Standard

- 中国船级社《钢质海船入级规范》第4篇第3章
Chapter 3, Part Four of China Classification Society Rules for Classification of Sea-Going Steel Ships
- IEC 60092-350:2020《船舶电气设备第350 部分:船舶与海上设施用电力、控制和仪表电缆的通用结构和试验要求》
IEC 60092-350: 2020 Electrical Installations in Ships-Part 350: General Construction and Test Methods of Power, Control and Instruction Cables for Shipboard and Offshore Applications
- IEC 60092-353:2016《船舶电气设备第353 部分:额定电压1kV 和3kV 电力电缆》
IEC 60092-353:2016 Electrical Installations in Ships-Part 353: Power Cables for Rated Voltages 1 kV and 3 kV

用于/Intended for

船舶/Ships

证书有效期至/This Certificate is valid until 2030年01月29日/ Jan. 29,2030

发证机构 中国船级社江苏分社
Issued by CCS/Jiangsu Branch

签发日期 2025年02月17日
Date Feb. 17,2025

本证书根据中国船级社规范和相关规定签发。所有证书页为一个整体，必须同时使用。纸质证书每页均须由本社盖章方为有效，电子证书含数字签名方为有效，本证书复印件无效。任何单位和个人均不应摘录或节选本证书的部分内容。有关方对所持证书的真实性有疑问时，可以向本社检验机构咨询。本证书凡是未注明版本的规范，其（发证时）最新版本适用于本证书。
This Certificate is issued pursuant to the Rules of the Society and related regulation. All pages of the certificate are taken as a whole and are used simultaneously. No paper certificate page is valid without bearing the stamp of the Society, no electronic certificates is valid without the digital signature, and no copied form of the certificate is regarded as valid. Any part of the certificate is not to be extracted or abridged by any unit or individual in any form. Related parties who are doubted about the authenticity of the certificate may inquire of the Society or its offices. For Rules with no version indication, their latest version (at the time of issuance of the certificate) applies to the this certificate.

Form No: W01.

联系方式/Contact Us, 见本社官方网站/See official web site of the Society (<http://www.ccs.org.cn>)



UTN:P024-32279886

产品明细/Product Description

船用低压电力电缆/Shipboard Low Voltage Power Cable(M0001)

名称/Name	属性(值)/Value	单位/Unit
产品名称/Product Name	见附页 See additional pages	
型号/Type	见附页 See additional pages	
规格/Specification	见附页 See additional pages	
导体最高工作温度/Max. Working Temp. of Conductor	见附页 See additional pages	
额定电压/Rated Voltage	见附页 See additional pages	V
燃烧特性/Characteristic Under Fire Conditions	见附页 See additional pages	

批准的图纸/Approved Drawings

图纸批准号/ Drawings Approval No. : NP13A00792, NP18A01308, NP19PPP03489

产品认可试验报告/ Approval Test Report

试验报告编号/ Test Report No. : CT12-2618-2/4~7, CT12-4877-1~4

试验报告日期/ Test Report Date : 2012-12-05

试验单位/ Laboratory: 国家电线电缆质量监督检验中心 China National Centre for Quality Supervision and Test of Electric Wire and Cable

试验单位地址/ Test Address: 上海市军工路1000号 No.1000, Jungong Road, Discrit, Shanghai

试验报告编号/ Test Report No. : CT16-3471-1~CT16-3471-4

试验报告日期/ Test Report Date : 2019-09-19

试验单位/ Laboratory: 国家电线电缆质量监督检验中心 China National Centre for Quality Supervision and Test of Electric Wire and Cable

试验单位地址/ Test Address: 上海市军工路1000号 No.1000, Jungong Road, Discrit, Shanghai

试验报告编号/ Test Report No. : TKJC20200028

试验报告日期/ Test Report Date : 2020-08-26

试验单位/ Laboratory: 安徽天康(集团)股份有限公司 Anhui Tiankang(Group) Shares Co.,Ltd.

试验单位地址/ Test Address: 安徽天长市仁和南路20号 No.20, South Renhe Road, Tianchang, Anhui

试验报告编号/ Test Report No. : TN20-3337

试验报告日期/ Test Report Date : 2020-09-15

试验单位/ Laboratory: 上海慧检测技术有限公司 Shanghai Intelligent Service and Technology Co.,Ltd.

试验单位地址/ Test Address: 上海市浦东新区金藏路258号2号楼一层 Floor 1, Building 2, No.258, Jinzang Road, Pudong New District, Shanghai

认可后的产品检验方式/Method of Product Inspection after Approval

按规范认可后应进行产品检验的产品/The product should be inspected in term of the rules:

认可后的产品检验应由本社验船师根据本社规范规定按批准的产品检验计划进行检验, 经检验合格后由本社颁发船用产品证书。

After approval, product inspection should be carried out by the Surveyor of the Society in accordance with the approved product inspection scheme, and the Marine Product Certificate will be issued by the Society upon satisfactory inspection.

认可保持条件/Maintenance Requirements of Approval

1. 工厂认可后, 如果图纸、技术文件、工艺规程有较大改变, 应征得本社同意。若改变涉及或影响到产品的设计、主要制造材料、关键工艺或产品的特性、特征, 则与特性有关的图纸和技术文件应经过本社审批, 并在检验机构认为必要时, 经本社检验人员到厂进行检查和见证有关试验, 其结果应能证实仍符合认可条件。

After works approval, if there are any major changes to the drawings, technical documents, specifications, prior consent should be obtained from the survey office of the Society. If the changes involve or affect product design, major construction materials, key workmanship or product characteristics and properties, drawings and technical documents related to properties are to be examined and approved by the Society and, where deemed necessary by the survey office, the surveyor to the Society will go to the manufacturer to inspect or witness relevant tests and the results of the tests should be able to demonstrate compliance with the approval conditions

2. 工厂的质量管理体系应保持有效运行，并且与认可时一致。如果质量管理体系发生改变，应经原体系认证机构审核并报本社批准。

The quality management system of the factory shall be ensure effective operation, and shall be the same as the situation of approval. If there are any changes to the quality management system, auditing of the original certification organization for quality management system and the society's approval shall be obtained.

3. 工厂认可证书获得者应接受本社每年一次的定期审核，定期审核日为认可证书期满之日对应的每一周年日，检查工作应在定期审核日的前后三个月内进行。

Those who have obtained the certificate of works approval shall receive periodical audit done by the Society on an annual basis. The date of periodical audit shall be each anniversary date which corresponds to the date of expiry of the relevant certificate and the periodical audit shall be done within a time span of three months before and after the annual surveillance date.

4. 在认可证书有效期内，本社检验人员可在未经事先通知的情况下对工厂的产品制造过程进行审核，以验证产品的生产是否符合业经本社批准的图纸和文件。工厂应予以配合。

Within the validity of the approval certificate, the surveyor to the Society may pay unannounced audit to the manufacturing process of the product in order to confirm whether it is in compliance with the drawings and documents approved by the Society. The factory should provide an active cooperation and necessary for the surveyor.

5. 认可证书有效期内，如果出现可能导致本社暂停或撤消认可的情况，工厂应及时采取有效的纠正措施。

Within the validity of the approval certificate, if cases occur that may cause the Society to suspend or withdraw the certificate, the manufacturer should take corrective actions in a prompt and effective manner.

备注/Remarks

1. 本社已审核了产品厂无石棉声明，但本社的审核不免除产品厂按照合同关系向订货方保证产品无石棉的责任。

The declaration of asbestos-free submitted by manufacturer has been reviewed by the Society. However, liability of the manufacturer to guarantee the products are asbestos-free to purchaser under contract will not be exempted.

2. 本证书由原工厂认可证书 (No. JS20PWA00136_01) 换新并替代原证书。

This certificate is renewed from and supersedes the previous Works Approval Certificate No. JS20PWA00136_01.

3. 生产地址/Manufacturing Address:

3.1 安徽省天长市滁州高新技术产业开发区天康工业园/Tiankang Industry Park, Chuzhou High-Tech Industrial Development Zone, Tianchang City, Anhui Province

3.2 安徽省天长市天康大道58号/No. 58, Tiankang Road, Tianchang City, Anhui Province

3.3 安徽省天长市铜城镇安乐社区长安中路/Changanzhong Road, Anle Community, Tongcheng Town, Tianchang City, Anhui Province

中国船级社江苏分社

CCS Jiangsu Branch

注：本证书含有附页，共2页

Note: The certificate is attached with additional 2 page(s)

产品明细
Product Description

1	产品名称/Names	乙丙橡胶绝缘船用电力电缆/Ethylene-propylene Rubber Insulated Shipboard Power Cables
	型号/Type	CEPF, CEPF86, CEPF96, CEPF80, CEPF90, CEPJ, CEPJ85, CEPJ95, CEPJ80, CEPJ90/SC, NC
		CEF, CEFR, CEF80, CEF90/SA, NA
	规格/Specification	单芯/Single-core: 1~240mm ² , 2芯/Two-core: 1~120mm ² , 3芯/Three-core: 1~185mm ² , 4~37芯/4~37-core: 1~2.5mm ²
	燃烧特性/Characteristic of Under Fire Condition	SC, NC, SA, NA
	导体最高工作温度/Max. Working Temp. of Conductor	90°C
	额定电压/Rated Voltage	0.6/1kV
2	产品名称/Names	交联聚乙烯绝缘船用电力电缆/ Cross-linked Polyethylene Insulated Shipboard Power Cables
	型号/Type	CJ86, CJ96, CJ85, CJ95, CJPJ, CJPJ85, CJPJ95, CJPJ80, CJPJ90, CJPF, CJPFR, CJPJ83, CJPJ86, CJPJ93, CJPJ96, CJPJ80, CJPJ90/SC, NC
		CJV, CJVR, CJV80, CJV90, CJV82, CJV92/SA, NA
	规格/Specification	单芯/Single-core:1~240mm ² , 2芯/Two-core: 1~120mm ² 3芯/Three-core: 1~185mm ² , 4~37芯/4~37-core: 1~2.5mm ²
	型号/Type	CJPFR85, CJPJR85, CJPFR86, CJPJR95/SC, NC
	规格/Specification	单芯/Single-core:1~240mm ² , 2芯/Two-core: 1~120mm ² , 3芯(3+1, 3+2)/3(3+1, 3+2)-core:1~185mm ² , 4-5芯/4~5-core: 1~50mm ² , 6~37芯/6~37-core: 1~2.5mm ²
	燃烧特性/Characteristic of Under Fire Condition	SC, NC, SA, NA
	导体最高工作温度/Max. Working Temp. of Conductor	90 °C
3	额定电压/Rated Voltage	0.6/1kV
	产品名称/Names	交联聚乙烯绝缘船用电线 Cross-linked Polyethylene Insulation Shipboard Electrical Wire
	型号/Type	CBYJR/DC
	规格/Specification	0.5~ 120mm ²
	燃烧特性/Characteristic of Under Fire Condition	DC
	导体最高工作温度/Max. Working Temp. of Conductor	90°C
	额定电压/Rated Voltage	0.6/1kV

注/Note:

产品型号中字母含义/Meaning of the letters of the Type:

- 字母 1/ 1st Letter: C -- 船用电力电缆/Shipboard Electric Power Cables;
CB -- 船用电线/Shipboard Wires;
- 字母 2/ 2nd Letter: J -- 交联聚乙烯绝缘/Cross-linked Polyethylene Insulation;
YJ -- 交联聚乙烯绝缘/Cross-linked Polyethylene Insulation;
E -- 乙丙橡皮绝缘/ Ethylene-propylene Rubber Insulation;
- 字母 3/ 3rd Letter: R -- 软结构 Soft Conductor
- 字母 4/ 4thLetter: F -- 氯丁橡胶护套或内护套/PCP Inner Sheath;
V -- 聚氯乙烯(ST2)护套或内护套/PVC(ST2) Inner Sheath;
PJ -- 交联聚烯烃护套或内护套（热固性）/Cross-linked PO Sheath;
PF -- 聚烯烃护套或内护套（热塑性）/PO-SHF1 Inner Sheath;
- 字母 5/ 5th Letter: 8 -- 镀锡(或不镀锡)铜丝编织 Tinned copper(or no tinned copper)wire braided;
9 -- 镀锌钢丝编织铠装/不锈钢丝编织铠装 Galvanized Steel Wires Braid;
- 字母 6/ 6th Letter: 0 -- 无外护套/Without Outer Sheath;
2 -- 聚氯乙烯(ST2)外护套/PVC(ST2) Outer Sheath;
3 -- 聚烯烃外护套(热塑型)/ PO-SHF1 Outer Sheath;
5 -- 交联聚烯烃外护套(热固型) Cross-linked PO outer sheath;
6 -- 聚烯烃护套(热塑型)/ PO-SHF1 Outer Sheath;
- 后缀/Trailing Suffix:
- SA -- 成束阻燃/Bunched Cable Flame Retardant(IEC 60332-3-22:2018);
- NA -- 耐火、成束阻燃/Bunched Cable Flame Retardant, Fire resistant (IEC 60331-1/2 (2018),
IEC 60332-3-22 Cat. A(2018));
- SC -- 成束阻燃、低烟、无卤/Bunched Cable Flame Retardant, Low Smoke,
Halogen Free (IEC 60332-3-22:2018, IEC 60754-1/2:2011, IEC 61034-1/2:2013);
- NC -- 成束阻燃、低烟、无卤、耐火/Bunched Cable Flame Retardant, Low Smoke, Halogen Free,
Fire resistant (IEC 60332-3-22:2018, IEC60331:2018, IEC 60754-1/2:2011, IEC 61034-1/2:2013);
- DC -- 单根阻燃、低烟、无卤/Single Cable Flame Retardant, Low Smoke and Halogen Free
(IEC 60332-1-2:2015, IEC 60754-1/2:2011, IEC 61034-1/2:2013)